Sponsor's Signature

WATER WELL REPORT DEPARTMENT OF ECOLOGY	Notice of Intent No. WE44773	SEI	
Type of Work: State of Washington	Unique Ecology Well ID Tag No. BNR420		
Construction	Site Well Name (if more than one well):  Water Right Permit/Certificate No.		
☐ Decommission ➡ Original installation NOI No	water Right Fermit Certificate 110.		
Proposed Use:	Property Owner Name LARRY THOMPSON		
The second of th	Well Street Address IBD HEINE ROAD		
Construction Type:   Method:     ■ New well   □ Alteration   □ Driven   □ Jetted   □ Cable Tool	City CHEWELAH County STEVENS		
☐ Deepening ☐ Other ☐ Dug ■ Air- ☐ Mud-Rotary	Tax Parcel No. 2572701		
Dimensions: Diameter of boring 6 in., to 250 ft.  Depth of completed well 250 ft.	Was a variance approved for this well? ☐ Yes ■ No		
Construction Details: Wall	If yes, what was the variance for?		
Casing Liner Diameter From To Thickness Steel PVC Welded Thread	Location (see instructions on page 2):	□ wwm	or EWM
	SE ½-½ of the SE ½; Section 05 Town		
ininininininin.	Latitude (Example: 47.12345) 48.29696		ge
	Longitude (Example: -120.12345) -117.78669		
Perforations: ☐ Yes ■ No Type of perforator used	Driller's Log/Construction or Decommission Procedure		
No. of perforations in. by in.  Perforated from ft. to ft. below ground surface	Formation: Describe by color, character, size of material and structure, and the kind and nature of the material in each layer penetrated, with at least one entry for each change of		
Screens: ☐ Yes ■ No ☐ K-Packer ➡ Depth ft.	information. Use additional sheets if necessary.	one entry for eac	ch change of
Manufacturer's Name	Material	From	То
Type Model No Diameter in. Slot size in. from ft. to ft.	OVERBURDEN	0	3
Diameter in. Slot size in. from ft. to ft.	TAN HARDPAN CLAY	3	18
Sand/Filter pack: ☐ Yes ■ No Size of pack material in.	GRAY CLAY	18	180
Materials placed from ft. to ft.	SILTY GRAY CLAY	180	240
Surface Seal: ■ Yes □ No To what depth? 18 ft.	GRAVELS SOME SAND HARD ROCK	240 250	250 250
Material used in seal BENTONITE	TIVILO NOON	200	200
Did any strata contain unusable water?   Yes No  Type of water?  Depth of strata			
Method of sealing strata off			-
Pump: Manufacturer's Name Type:			
H.P Pump intake depth: ft. Designed flow rate: gpm			1
Water Levels: Land-surface elevation above mean sea level 1649 ft.			
Stick-up of top of well casing ft. above ground surface Static water level 3 ft. below top of well casing Date 06/30/2021			
Artesian pressure lbs. per square inch			
Artesian water is controlled by (cap, valve, etc.)		-	
Well Tests:			
Was a pumping test performed? ■ No ☐ Yes ⇒ by whom? Yield gpm with ft. drawdown after hrs.			
Yieldgpm with ft. drawdown after hrs.			
Yield gpm with ft. drawdown after hrs.			
Recovery data (time = zero when pump is turned off – water level measured from well top to water level)			
Time Water Level Time Water Level Time Water Level			
Date of pumping test		-	
Air test 30 gpm with stem set at 248 ft. for 1 hrs. Date 06/29/2021			
Artesian flow gpm			1
Temperature of water ° F Was a chemical analysis made? ☐ Yes ■ No	Start Date <u>06/28/2021</u> Completed Date <u>06/29/2021</u>		
WELL CONSTRUCTION CERTIFICATION: I constructed and/or accept responsibility for construction of this well, and its compliance with all Washington well construction standards. Materials used and the information reported above are true to my best knowledge and belief.			
■ Driller □ Trainee □ PE – Print Name AUSTIN GEE	Drilling Company FOGLE PUMP & SUPPLY, INC.		
Signature Again	Address 2250 NORTH HIGHWAY		
License No. 3335	City, State, Zip COLVILLE, WA 99114		
IF TRAINEE: Sponsor's License No.	Contractor's		

Registration No. FOGLEPS095L4

Date 06/29/2021